



- SMD LVDS VCXO 5.0×3.2mm
 - Differential output LVDS
 - Available 3-State function
 - Low jitter
 - Mode : Fundamental, Multi
- Applications : Radio transmitter - receiver equipment. Optical transmission device, Digital image devices.

Standard Specification

Frequency Range	1.000MHZ to 80.000MHZ (Fund)	0.75MHZ to 800.000MHZ (multi)
Supply voltage	2.5V, 3.3V	3.3V
Pin 1 Control voltage	1.25V±1.05V (1.25V)	1.65V±1.35V (1.65V)
Frequency Deviation	±100ppm min	
Linearity	10% max	
Slope	Positive	
Current consumption	80mA max	
Temperature Range	Operating	-40°C to +85°C, User spec
	Storage	-55°C to +125°C
Frequency Stability	±50ppm max, User spec	
Output load condition	100Ω OUT - OUTN	
Symmetry (Duty)	45% to 55%	
Output rise and fall time (tr/ft)	1ns max (20% ~ 80% Ouput Level)	
OE High / OE Low	0.7Vdd min / 0.3Vdd max	
High output voltage	1.4V min ~ 1.6V max	
Low output voltage	0.9V min ~ 1.1V max	
Pin 2 Input voltage	No Connection (Default)	
Pin 2 Input voltage	70% Vdd min (Output enable)	
Pin 2 Input voltage	30% Vdd max (Output disable)	
Output Differential Voltage	0.247V ~0.454V	
Offset Voltage	1.125V ~ 1.375V	
Oscillation start up time	5ms max	
Aging	± 3ppm max	
phase Jitter (12KHZ ~20MHZ)	1ps max	4ps max

Dimensions (mm)

