



■ S15M15A ~ S45M30A

- Compact and light Ceramic SMD MCF
- Outstanding vibration and shock resistant characteristics
- Suitable for automatic mounting and reflow soldering

■ Standard Specification

Model	Nominal Frequency (MHz)	Passband Width		Stopband Width		Ripple (dB)	Insertion Loss (dB)	Guaranteed Attenuation (dB)	Terminating Impedance (kΩ//pF)	Package
		(dB)	(kHz)	(dB)	(kHz)					
S17M15A	17.9	3	±7.5	17	±25	0.75	2.0	65	1.8//1.9	S-1
S21M7.5A	21.4	3	±3.75	18	±15	1	2.0	65	0.87//6.0	S-1
S21M15A	21.4	3	±7.50	18	±25	0.5	1.5	65	1.5//2.5	S-1
21.7M7.5A	21.7	3	±3.75	18	±15	1	2.0	65	0.87//6.0	S-1
21.7M15A	21.7	3	±7.50	18	±25	0.5	1.5	65	1.5//2.5	S-1
S45M15A	45	3	±7.50	15	±25	1	2.0	60	0.56//6.0	S-1
S45M30A	45	3	±15	15	±50	1	3.0	65	1.2//1.5	S-1

■ Dimensions (mm)

